

Contents

Vergnet presentation

Hybridization

Projects insights

Les Saintes

Nouadhibou

Yap


Conclusion



Vergnet presentation



• Location Ormes (France — Orléans)







- Location Ormes (France Orléans)
 - Subsidiaries in the Caribbean, Indian Ocean, Pacific, Africa







- Location Ormes (France Orléans)
 - Subsidiaries in the Caribbean, Indian Ocean, Pacific, Africa
- Staff of 100 of which 60% in design, engineering and O&M







- Location Ormes (France Orléans)
 - Subsidiaries in the Caribbean, Indian Ocean, Pacific, Africa
- Staff of 100 of which 60% in design, engineering and O&M
- 25 years experience in difficult and isolated areas







- Location Ormes (France Orléans)
 - Subsidiaries in the Caribbean, Indian Ocean, Pacific, Africa
- Staff of 100 of which 60% in design, engineering and O&M
- 25 years experience in difficult and isolated areas
- 365 MW installed (Wind and PV) in 40 countries









We are all here to speak about Hybrid, we all have an idea of what is means



We are all here to speak about Hybrid, we all have an idea of what is means

but



We are all here to speak about Hybrid, we all have an idea of what is means

but

There doesn't seem to be a *precise* definition of what a power hybrid system is



We are all here to speak about Hybrid, we all have an idea of what is means

but

There doesn't seem to be a *precise* definition of what a power hybrid system is

Saying an hybrid grid is a grid with renewable energy is not enough,



We are all here to speak about Hybrid, we all have an idea of what is means

but

There doesn't seem to be a *precise* definition of what a power hybrid system is

Saying an hybrid grid is a grid with renewable energy is not enough,

Connecting a 500kW solar plant to a 5MW diesel grid is not what we call hybridization at VERGNET.



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:





We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

Examples

Thermal gensets operational limits



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

- Thermal gensets operational limits
- Spinning reserve



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

- Thermal gensets operational limits
- Spinning reserve
- RE Power excess (when battery grid forming)





We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

- Thermal gensets operational limits
- Spinning reserve
- RE Power excess (when battery grid forming)
- Voltage regulation



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

- Thermal gensets operational limits
- Spinning reserve
- RE Power excess (when battery grid forming)
- Voltage regulation
- · Frequency regulation



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

- · Thermal gensets operational limits
- Spinning reserve
- RE Power excess (when battery grid forming)
- Voltage regulation
- Frequency regulation
- Grid safety



We consider an installation to be hybrid if for a reason or another a curtailment of renewable energy is required:

- Thermal gensets operational limits
- Spinning reserve
- RE Power excess (when battery grid forming)
- Voltage regulation
- Frequency regulation
- Grid safety
- Power quality (Harmonics, flicker)



0/20

Isolated grids key issues



Small Islands grids are characterized by:

Small installed power





- Small installed power
- Low short circuit power



- Small installed power
- Low short circuit power
- Small spinning reserve



- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power

- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power
- N-1 contingency rarely used for diesels



- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power
- N-1 contingency rarely used for diesels



Small Islands grids are characterized by:

- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power
- N-1 contingency rarely used for diesels

Theses specificities lead to potentially high variations of voltage and frequency in case of grid fault or power producer failure.



Small Islands grids are characterized by:

- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power
- N-1 contingency rarely used for diesels

Theses specificities lead to potentially high variations of voltage and frequency in case of grid fault or power producer failure.

Grid security can be an issue when adding renewables



Small Islands grids are characterized by:

- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power
- N-1 contingency rarely used for diesels

Theses specificities lead to potentially high variations of voltage and frequency in case of grid fault or power producer failure.

Grid security can be an issue when adding renewables

• Shord circuit power can be too low to trip existing protections



Small Islands grids are characterized by:

- Small installed power
- Low short circuit power
- Small spinning reserve
- High ratio peak demand short circuit power
- N-1 contingency rarely used for diesels

Theses specificities lead to potentially high variations of voltage and frequency in case of grid fault or power producer failure.

Grid security can be an issue when adding renewables

- Shord circuit power can be too low to trip existing protections
- Specific grid protections have to be designed and properly set



Projects insights



Power hybrid systems by Vergnet

Vergnet has a long experience in connecting unpredictable renewable energy producers to weak grids: first installation of wind turbines on an small island diesel grid in 1989.

Date	Name	Location	Renewables P	Diesel P	Grid P	Remark
2018	Amdjaras	Chad	1.1 MW wind	500 kW	700 kW	300 kW/2.5 MWh storage Grid forming
2018	Yap	Micronesia	1.5 MW wind & PV	3x1.6 MW	grid 2MW max	
2017	Kiffa	Mauritania	1.3 MW PV			
2015	Bonriki	Kiribati	1.3 MW PV	55MW		
2013	Nouadhibou	Mauritania	4.4 MW wind	16 MW		
2013	Devil's point	Vanuatu	3.5 MW wind			
2011	Marsabit	Kenya	0.5 MW wind	2.4 MW		
2009	El Toqui	Chile	1.5 MW wind	6 MW		
2007	Coral Bay	Australia	825 kW			Low load diesel + Flywheel (Powercorp
2005	Les Saintes	French Carribean	1.9 MW			



Connection issues







Connection issues

Impedance at point of common coupling was too high, this was the first time VERGNET encountered hybridization issues and a very trivial form of automatic regulation had to be implemented:



Connection issues

Impedance at point of common coupling was too high, this was the first time VERGNET encountered hybridization issues and a very trivial form of automatic regulation had to be implemented:



solution



Connection issues

Impedance at point of common coupling was too high, this was the first time VERGNET encountered hybridization issues and a very trivial form of automatic regulation had to be implemented:



solution

Voltage regulation at turbine level



Connection issues

Impedance at point of common coupling was too high, this was the first time VERGNET encountered hybridization issues and a very trivial form of automatic regulation had to be implemented:



solution

- Voltage regulation at turbine level
- · A power limitation had to be implemented



Connection issues

Impedance at point of common coupling was too high, this was the first time VERGNET encountered hybridization issues and a very trivial form of automatic regulation had to be implemented:



solution

- Voltage regulation at turbine level
- · A power limitation had to be implemented
- Utility agreeded on a downgraded $\cos \phi$



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



Site conditions

• Wind speed 8.78 m s⁻¹ at hub height, Weibull 3.63



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



- Wind speed 8.78 m s⁻¹ at hub height, Weibull 3.63
- · Near shore, hot climate, no rain, very high corrosion, sand



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



- Wind speed 8.78 m s⁻¹ at hub height, Weibull 3.63
- Near shore, hot climate, no rain, very high corrosion, sand
- Average load 5.5 MW, max load 10 MW



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



- Wind speed 8.78 m s⁻¹ at hub height, Weibull 3.63
- · Near shore, hot climate, no rain, very high corrosion, sand
- Average load 5.5 MW, max load 10 MW
- 4×4 MW diesel gensets



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



- Wind speed 8.78 m s⁻¹ at hub height, Weibull 3.63
- · Near shore, hot climate, no rain, very high corrosion, sand
- Average load 5.5 MW, max load 10 MW
- 4×4 MW diesel gensets



SNIM iron ore terminal

More than 12 Mt of ore per year is transported by train from the mines to Nouadhibou harbor to be loaded and exported by sea.



Site conditions

- Wind speed 8.78 m s⁻¹ at hub height, Weibull 3.63
- Near shore, hot climate, no rain, very high corrosion, sand
- Average load 5.5 MW, max load 10 MW
- 4×4 MW diesel gensets

An EPC tender was issued in 2010.



VERGNET proposed a full grid study

To assess and guarantee the achievable wind power penetration according to wind profile, grid load cycles and diesel gensets characteristics while ensuring:



VERGNET proposed a full grid study

To assess and guarantee the achievable wind power penetration according to wind profile, grid load cycles and diesel gensets characteristics while ensuring:

Security of goods and persons



VERGNET proposed a full grid study

To assess and guarantee the achievable wind power penetration according to wind profile, grid load cycles and diesel gensets characteristics while ensuring:

- Security of goods and persons
- Availability of the grid

VERGNET proposed a full grid study

To assess and guarantee the achievable wind power penetration according to wind profile, grid load cycles and diesel gensets characteristics while ensuring:

- Security of goods and persons
- Availability of the grid
- Power quality





The studies covered the following points:

 On site measurement session to precisely characterize the gensets performances



- On site measurement session to precisely characterize the gensets performances
- Numeric modeling of the whole grid with producers and consumers



- On site measurement session to precisely characterize the gensets performances
- Numeric modeling of the whole grid with producers and consumers
- Simulation campaign addressing all possible cases



- On site measurement session to precisely characterize the gensets performances
- Numeric modeling of the whole grid with producers and consumers
- Simulation campaign addressing all possible cases
- Diesel-Wind power plant operating rules definition from analysis of simulation results





The behavior of the diesel power plant and wind power plant was checked during both normal and unforeseen transient events like:

Disconnection of one or several wind turbines



- Disconnection of one or several wind turbines
- Disconnection of the whole wind power plant

- Disconnection of one or several wind turbines
- Disconnection of the whole wind power plant
- Starting of power loads

- Disconnection of one or several wind turbines
- Disconnection of the whole wind power plant
- Starting of power loads
- Disconnection of loads



- Disconnection of one or several wind turbines
- Disconnection of the whole wind power plant
- Starting of power loads
- Disconnection of loads
- Disconnection of a diesel group



- Disconnection of one or several wind turbines
- Disconnection of the whole wind power plant
- Starting of power loads
- Disconnection of loads
- Disconnection of a diesel group



The behavior of the diesel power plant and wind power plant was checked during both normal and unforeseen transient events like:

- Disconnection of one or several wind turbines
- Disconnection of the whole wind power plant
- Starting of power loads
- Disconnection of loads
- Disconnection of a diesel group

Customer did not allow a full automation of diesel Genset so operating values are set by operators, a set of operating rules were defined to set the wind power plant power level according to grid state.



Nouadhibou, Mauritania — Results

We define the penetration ratio r by :

$$r = \frac{P_W}{P_L} \times 100 \tag{1}$$

Where P_W is wind power, P_L is load power.


"\times" represents cases with a blackout risk due to lack of spinning reserve
"\times" represents impossible cases.

Load (kW)	Nb running groups		
	1	2	3
1000	20.0%	Θ	Θ
1500	46.7%	⊝	Θ
2000	38.3%	20.0%	Θ
2500	30.6%	36.0%	4.0%
3000	25.5%	46.7%	20.0%
3500	21.9%	43.7%	31.4%
4000	19.1%	38.3%	40.0%
4500	Δ	34.0%	46.7%
5000	Δ	30.6%	45.9%
5500	Δ	27.8%	41.7%
6000	Δ	25.5%	38.3%
6500	Δ	23.5%	35.3%
7000	Δ	21.9%	32.8%
7500	Δ	20.4%	30.6%
8000	Δ	19.1%	28.7%
8500	Θ	Δ	27.0%
9000	Θ	Δ	25.5%
9500	⊝	Δ	24.2%
10000	Θ	Δ	23.0%

Achievable long term penetration ratio



very good results are achieved thanks to exceptional site conditions.



1.5 year daily penetration record, 7 days average

- Wind power plant output: 19 GW h year⁻¹
- Fuel savings: 4800 t year⁻¹
- Pollution avoided (CO₂, NO_x, SO₂): 11 500 t year⁻¹



Yap, F.S.Micronesia — Commissionned 2017

Tender citation

"The goal for integration and control system is to achieve highest possible renewable energy penetration, while maintaining power system stability and electric energy supply reliability at the same time. To ensure this, the integration and control system will take control over all other components in Yap power system, scheduling of diesel generators, and dispatching wind and solar generation..."





Yap, F.S.Micronesia — System architecture


Architecture



Yap, F.S.Micronesia — System architecture

Architecture


3 wind turbines




Yap, F.S.Micronesia — System architecture

Architecture


- 3 wind turbines
- Automation of Gensets




- 3 wind turbines
- · Automation of Gensets
- Island power management




- 3 wind turbines
- Automation of Gensets
- Island power management
- Wireless communication with solar plants



- 3 wind turbines
- Automation of Gensets
- Island power management
- Wireless communication with solar plants
- Power analysers at grid key points




- 3 wind turbines
- Automation of Gensets
- Island power management
- Wireless communication with solar plants
- Power analysers at grid key points



Architecture


- 3 wind turbines
- Automation of Gensets
- Island power management
- Wireless communication with solar plants
- Power analysers at grid key points



Grid study similar as Nouadhibou was performed.




Controller





Controller






Controller

Hybrid Wizard is the result of Vergnet's experience

 Real-time control of Power Quality



Controller

- Real-time control of Power Quality
- RE penetration is always maximized to what the grid can accept



Controller


- Real-time control of Power Quality
- RE penetration is always maximized to what the grid can accept
- Grid stability is guaranteed





Controller


- Real-time control of Power Quality
- RE penetration is always maximized to what the grid can accept
- · Grid stability is guaranteed
- Grid security is guaranteed




Yap, F.S.Micronesia — Studies

Expected performances

At bid time a simple load flow study was performed to assess performances



Above is heat map of connected diesels without and with renewable energy. Below is expected penetration rate. Data is on one month to remain legible.



Yap, F.S.Micronesia — First results



- Wind power plant output: 2.1 GW h year⁻¹
- Solar power plants output: 1.2 GW h year⁻¹
- Expected Fuel savings: 730 t year⁻¹





 Most existing installations have a huge installed diesel power with too powerfull gensets for fine adjustment of spinning reserve.



- Most existing installations have a huge installed diesel power with too powerfull gensets for fine adjustment of spinning reserve.
- Preparation work from a consultant is paramount in tenders, for mutual agreements, companies must be competent or subcontract.



- Most existing installations have a huge installed diesel power with too powerfull gensets for fine adjustment of spinning reserve.
- Preparation work from a consultant is paramount in tenders, for mutual agreements, companies must be competent or subcontract.
- Take Operation & Maintenance into account since the very beginning of the project.



- Most existing installations have a huge installed diesel power with too powerfull gensets for fine adjustment of spinning reserve.
- Preparation work from a consultant is paramount in tenders, for mutual agreements, companies must be competent or subcontract.
- Take Operation & Maintenance into account since the very beginning of the project.
 - Technological choices and targets must fit to the local capability and infrastructures.



- Most existing installations have a huge installed diesel power with too powerfull gensets for fine adjustment of spinning reserve.
- Preparation work from a consultant is paramount in tenders, for mutual agreements, companies must be competent or subcontract.
- Take Operation & Maintenance into account since the very beginning of the project.
 - Technological choices and targets must fit to the local capability and infrastructures.
 - If knowhow is not already present, include a capability building programme



Thank you for your attention



